

soundsense cc3.0

Soundsense CC3.0 is an acoustic underlay for use under carpet tiles, sheet vinyl, click LVT and linoleum. It provides excellent impact sound reduction under these floors and offers long lasting performance.

soundsense cc3.0 technical information

Soundsense CC3.0 is ideal in installations where a variety of finished floors are to be used and where there is a requirement for a permanent resilient layer to provide impact sound reduction.

Specification

Characteristic	Result	Test Method
Roll dimensions	1 x 15m - 15m ²	BS 5808:1991
Thickness	3mm	BS 4051:1987
Weight	1.8kg/m ²	ISO 7322:2014
Density	600kg/m ³	ISO 7322:2014
Tensile strength	780kPa	ISO 7322:2014
Compression	15%	ASTM F36
Recovery from compression	>75%	ASTM F36
Tog rating	0.33	
Operating temperature range	-30 to 90°C	

Acoustic performance

Finished floor	Result	Test Method
Carpet Tiles	33dB	ISO 10140-3:2010
Sheet Vinyl	20dB	ISO 10140-3:2010
Linoleum	18dB	ISO 10140-3:2010
Click LVT	17dB	ISO 10140-3:2010
Dynamic Stiffness	125MN/m ³	ISO 9052-1:1989

FOOTFALL | EVERYTHING FOR
A QUIET LIFE

0333 323 4570 | footfalluk.co.uk

Footfall Flooring Ltd Unit 4, Witton Business Park, Cartmel Road, Blackburn BB2 2TA

soundsense cc3.0 features and benefits

Designed for use under any finished floor*

Carpet tile 33dB

Vinyl 20dB

Linoleum 18dB

LVT 17dB

Soundsense CC3.0

Concrete

Complies with Building Regulations

minimum 17dB impact sound improvement



Cost effective to install



Available nationwide through most flooring distributors



10 year in-use warranty

Environmentally friendly

made from cork stopper waste and recycled vehicle tyres



Permanent solution forms part of building structure



Ideal for under-floor heating low Tog rating 0.33



Balanced density for lasting performance



Capability to cover slight subfloor imperfections



*except ceramic tile

For further information call Technical Support on 0333 323 4570

footfalluk.co.uk